



Metal Film Resistors



	0207	0204
L ₁ [mm]	6,3 ±0,3	3,4 ±0,3
D [mm]	2,4 ±0,2	1,9 ±0,2
d [mm]	0,6 ±0,05	0,5 ±0,05

Technical parameters:	RM	RMM
Case Size	0207	0204
Power Rating at 70°C	0,6W	0,4W
Resistance Tolerance	1%(<1R:5%)	1%(<1R:5%)
Temperature Coefficient	50ppm	50ppm
Max. Working Voltage	300 V	200 V
Insulation Voltage	500 V	500 V
Insulation Resistance	> 10GΩ	> 10GΩ
Marking	IEC colour code-5bands	
Package	bandoliered on tape: 5000 pcs	
Manufact. Part Number	MF0207	MF0204
How to order	RM 1% 2,2K	RMM 1% 2,2K

Minimum ordering quantity 500pcs is intended for items which are marked by "O"

Ohmic Value	RM	RMM
0 R	S 20004	
0,22 R	S 22954	
0,33 R	S 22958	
0,47 R	S 22962	
1 R	S 30615	O 57955
1,2 R	S 30617	O 57956
1,5 R	S 30619	O 57957
1,8 R	S 30621	O 57960
2,2 R	S 30623	O 57961
2,7 R	S 30625	O 57962
3,3 R	S 30627	O 57963
3,9 R	S 30629	O 57964
4,7 R	S 30631	O 57965
5,6 R	S 30633	O 26818
6,8 R	S 30635	O 26820
8,2 R	S 30637	S 26822
10 R	S 30639	S 26236
12 R	S 30647	O 26238
13 R	O 30651	O 26239
15 R	S 30657	S 26240
16 R	O 30660	O 26241
18 R	S 30666	O 26242
20 R	S 30671	O 26243
22 R	S 30675	S 26244
24 R	S 30680	O 26245
27 R	S 30686	O 26246
33 R	S 30696	S 26248
39 R	S 30705	O 26250
47 R	S 30715	S 26252
51 R	S 30719	O 26253
56 R	S 30724	S 26254
62 R	S 30730	O 26255
68 R	S 30734	S 26256
75 R	S 30739	O 26257
82 R	S 30743	S 26258
91 R	S 30749	O 26259
100 R	S 30753	S 26260
110 R	S 30757	O 26261
120 R	S 30761	S 26262
130 R	S 30765	O 26263
150 R	S 30771	S 26264
160 R	S 30774	O 26265
180 R	S 30780	S 26266
200 R	S 30785	O 26267
220 R	S 30789	S 26268

Ohmic Value	RM	RMM
240 R	S 30794	O 26269
270 R	S 30800	S 26270
300 R	S 30805	O 26271
330 R	S 30810	S 26272
360 R	S 30815	O 26273
390 R	S 30819	S 26274
430 R	S 30824	O 26275
470 R	S 30829	S 26276
499 R	S 30832	O 68555
510 R	S 30833	O 26277
560 R	S 30838	S 26278
620 R	S 30844	O 26279
680 R	S 30848	S 26280
750 R	S 30853	O 26281
820 R	S 30857	S 26282
910 R	S 30863	O 26283
1 K	S 30867	S 26284
1,1 K	S 30871	O 26285
1,2 K	S 30875	S 26286
1,3 K	S 30879	O 26287
1,5 K	S 30885	S 26288
1,6 K	S 30888	O 26289
1,8 K	S 30894	S 26290
2 K	S 30899	O 26291
2,2 K	S 30903	S 26292
2,4 K	S 30908	O 26293
2,7 K	S 30914	S 26294
3 K	S 30919	O 26295
3,3 K	S 30924	S 26296
3,6 K	S 30929	O 26297
3,9 K	S 30933	S 26298
4,3 K	S 30938	O 26299
4,7 K	S 30943	S 26300
5,1 K	S 30947	O 26301
5,6 K	S 30952	S 26302
6,2 K	S 30958	O 26356
6,8 K	S 30962	S 26303
7,5 K	S 30967	O 26304
8,2 K	S 30971	S 26305
9,1 K	S 30977	O 26306
10 K	S 30981	S 26307
11 K	S 30985	O 26308
12 K	S 30989	S 26309
13 K	S 30993	O 26310
15 K	S 30999	S 26311

Ohmic Value	RM	RMM
22 K	S 31017	S 26315
24 K	S 31022	O 26316
27 K	S 31028	S 26317
30 K	S 31033	O 26318
33 K	S 31038	S 26319
36 K	S 31043	O 26320
39 K	S 31047	S 26321
43 K	S 31052	O 26322
47 K	S 31057	S 26323
51 K	S 31061	O 26324
56 K	S 31066	S 26325
62 K	S 31072	O 26326
68 K	S 31076	S 26327
75 K	S 31081	O 26328
82 K	S 31085	S 26329
91 K	S 31091	O 26330
100 K	S 31095	S 26331
110 K	S 31099	O 26332
120 K	S 31103	S 26333
150 K	S 31113	S 26335
180 K	S 31122	O 26337
200 K	S 31127	O 26338
220 K	S 31131	S 26339
270 K	S 31142	O 26341
330 K	S 31152	S 26343
390 K	S 31161	O 26345
470 K	S 31171	S 26347
560 K	S 31180	O 26349
680 K	S 31190	S 26351
750 K	S 31195	O 26352
820 K	S 31199	O 26353
910 K	S 31205	O 26354
1 M	S 31209	S 26355
1,2 M	S 31211	
1,5 M	S 31213	
1,8 M	S 31215	
2,2 M	S 31217	
2,7 M	S 31219	
3,3 M	S 31221	
3,9 M	S 31223	
4,7 M	S 31225	
5,6 M	S 31227	
6,8 M	S 31229	
8,2 M	S 31231	
10 M	S 31233	