


ELST Series

ELST x008 V



Technical Parameters	ELST 3008 V	ELST 4008 V
Marking *	RSMC 3	RSMC 4
Type	straight plug	straight plug
Number of contacts	3	4
Conductor size	0,14 - 0,34 mm ²	0,14 - 0,34 mm ²
Cable diameter	4 - 5 mm	4 - 5 mm
Rated voltage	60 V AC/DC	20 V AC/DC
Rated current	3 A	4 A
Type of termination	pin penetration	pin penetration
Protection class	IP67	IP67
Operating temperature	-25°C to 70°C	-25°C to 70°C

* Alternative supplies also marked as LUMBERG. Hirschmann and Lumberg companies belong to the BELDEN group.

Part No.	Manuf. No.	Ord.No.
S ELST 3008 V	933406-100	51408
S ELST 4008 V	933407-100	57407

ELST 4012 PG7



ELST 4012 PG9



Technical Parameters	ELST 4012 PG7	ELST 4012 PG9
Marking *	RSC 4/7	RSC 4/9
Type	straight plug	straight plug
Number of contacts	4	4
Conductor size	max. 0,75 mm ²	max. 0,75 mm ²
Cable diameter	4 - 6 mm	6 - 8 mm
Rated voltage	250 V AC/DC	250 V AC/DC
Rated current	4 A	4 A
Type of termination	screw	screw
Protection class	IP67	IP67
Operating temperature	-25°C to 90°C	-25°C to 90°C

* Alternative supplies also marked as LUMBERG. Hirschmann and Lumberg companies belong to the BELDEN group.


Part No.	Manuf. No.	Ord.No.
S ELST 4012 PG7	933098-100	38132
S ELST 4012 PG9	933162-100	50343

ELWIKA Series

ELWIKA 4012 PG7 Black



ELWIKA 4012 PG9



Technical Parameters	ELWIKA 4012 PG7	ELWIKA 4012 PG9
Marking *	RKCW 4/7	RKCW 4/9
Type	angled socket	angled socket
Number of contacts	4	4
Conductor size	max. 0,75 mm ²	max. 0,75 mm ²
Cable diameter	4 - 6 mm	6 - 8 mm
Rated voltage	250 V AC/DC	250 V AC/DC
Rated current	4 A	4 A
Type of termination	screw	screw
Protection class	IP67	IP67
Operating temperature	-25°C to 90°C	-25°C to 90°C

* Alternative supplies also marked as LUMBERG. Hirschmann and Lumberg companies belong to the BELDEN group.

Part No.	Manuf. No.	Ord.No.
S ELWIKA 4012 PG7	933172-100	38130
S ELWIKA 4012 PG9	933174-100	1648

ELWIKA 5012 PG9 Black



Technical Parameters	ELWIKA 5012 PG9 Black
Marking *	RKCW 5/9
Type	angled socket
Number of contacts	5
Conductor size	max. 0,75 mm ²
Cable diameter	6 - 8 mm
Rated voltage	50 V AC/DC
Rated current	4 A
Type of termination	screw
Protection class	IP67
Operating temperature	-25°C to 90°C

* Alternative supplies also marked as LUMBERG. Hirschmann and Lumberg companies belong to the BELDEN group.

Part No.	Manuf. No.	Ord.No.
S ELWIKA 5012 PG9 Black	933176-100	71978

ELWIST Series

ELWIST 4012 PG7



ELWIST 4012 PG9



Technical Parameters	ELWIST 4012 PG7	ELWIST 4012 PG9
Marking *	RSCW 4/7	RSCW 4/9
Type	angled plug	angled plug
Number of contacts	4	4
Conductor size	max. 0,75 mm ²	max. 0,75 mm ²
Cable diameter	4 - 6 mm	6 - 8 mm
Rated voltage	250 V AC/DC	250 V AC/DC
Rated current	4 A	4 A
Type of termination	screw	screw
Protection class	IP67	IP67
Operating temperature	-25°C to 90°C	-25°C to 90°C

* Alternative supplies also marked as LUMBERG. Hirschmann and Lumberg companies belong to the BELDEN group.

Part No.	Manuf. No.	Ord.No.
S ELWIST 4012 PG7	933165-100	38131
S ELWIST 4012 PG9	933166-100	51121