



ΔV



**MW 3279**  
CamPlus-Intercept 30mins Super fast battery charger with 4 Channels DV control DV detection 4 channels For AA, AAA Ni-Cd/Ni-MH batteries  
**Accessories:**  
car adaptor MWCP1  
switching adaptor MW 7M25GS



Technical Parameters		MW 3279
Input Voltage	AC 100-230V , DC 12-13.8V	
Battery Type	Ni-Cd/Ni-MH	
Battery Size	AAA, AA	
Charging Current - fast charge	3000mA (AA), 1200mA (AAA)	
Charging Current - trickle charge	300mA (AA), 120mA (AAA)	
Discharge function	no	
Input Method	Cigarette Lighter Plug for car	
Dimension	128x82x50mm	

Part No.	Ord.No.
S MW 3279	70395



ΔV

LCD



**MW 6278**  
Universal Ni-Cd/Ni-MH Battery Charger with LCD Display, 4 Channels DV Control and Discharge 4 channels Desktop For 1-4 pcs AA, AAA, C, D or 1-2 pcs 9V Ni-Cd/Ni-MH batteries  
**Accessories:**  
car adaptor MWCP1  
switching adaptor MW 7E12



Technical Parameters		MW 6278
Input Voltage	AC 100-240V	
Battery Type	Ni-Cd/Ni-MH	
Battery Size	AAA, AA, C, D, 9V	
Charging Current - fast charge	1000mA (AA,C,D), 500mA(AAA),13mA PP3 (9V)	
Charging Current - trickle charge	100mA (AA,C,D), 50mA (AAA)	
Discharge function	yes	
Input Method	Desktop, Others	
Dimension	190x128.5x61mm	

Part No.	Ord.No.
S MW 6278	70397



ΔV

**MW 6288 GS**  
Plug-in 9V Battery Charger w/ DV and Discharge Function DV detection Discharge function 2 channels For 9V Ni-Cd/Ni-MH batteries Plug-in



Technical Parameters		MW 6288 GS
Input Voltage	AC 230V	
Battery Type	Ni-Cd/Ni-MH	
Battery Size	Block 9V	
Charging Current - fast charge	70mA	
Charging Current - trickle charge	7mA	
Discharge function	no	
Input Method	Plug-In	
Dimension	98x64x91.75mm	

Part No.	Ord.No.
S MW 6278	70396

## USB Battery Chargers



USB

**MW U112**  
USB Charger Portable Extendable For 1 or 2pcs Ni-Cd/Ni-MH batteries  
**Accessories:**  
car adaptor MWCP1  
switching adaptor MW 7M25GS



Technical Parameters		MW U112
Input Voltage	5V	
Battery Type	Ni-Cd/Ni-MH	
Battery Size	AA/AAA	
Charging Current	200 mA	
Discharge function	no	
Input Method	Plug-In	
Dimension	20 x 17 x 87.6mm	

Part No.	Ord.No.
S MW U112	70398

## Alkaline Battery Chargers

Special chargers for Rechargeable Alkaline Manganese batteries (RAM). Warranty for RAM batteries is relevant to the use with these chargers.



μController

**AccuCell**  
**ACL62**  
Rapid charger for 1-4 alkaline AA/AAA RAM (rechargeable alkaline-manganese) batteries. A microcontroller monitors each bay separately to ensure that each cell is charged effectively, and protected against overcharging and reverse polarity. After charging it changes over automatically to trickle charge.

Technical Parameters		ACL62
Input Voltage	230V	
Battery Type	RAM	
Battery Size	AAA/AA	
No. of Batteries	1-4	
Max. charging current per bay:	400mA	
Typ. charging time for 2000 mAh AA bat.	320min.	
Processor	yes	
Dimension (WxHxD)	83 x 125 x 75 mm	

Part No.	Ord.No.
S ACL62	57505



μController

**AccuCell**  
**ACL64**  
Universal rapid charger for 1-4 RAM (Rechargeable Alkaline Manganese) batteries: AA, AAA, C or D. A microcontroller monitors each bay separately to ensure that each cell is charged effectively, and protected against overcharging and reverse polarity. After charging it changes over automatically to trickle charge.

Technical Parameters		ACL64
Input Voltage	230V	
Battery Type	RAM	
Battery Size	AAA/AA/C/D	
No. of Batteries	1-4	
Max. charging current per bay:	500mA	
Typ. charging time for 2000 mAh AA bat.	250min.	
Processor	yes	
Dimension (WxHxD)	105 x 205 x 60 mm	

Part No.	Ord.No.
O ACL64	57506