



Fuse Holder - Stackable version - Pitch 10mm - 01÷05 poles

GENERAL INFORMATION

pitch:	10 mm
housing height:	19,00 mm
housing depth:	26.4 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	ø- mm
wire stripping:	max 10 mm
operating temperature:	-25°C ÷ +100°C

ELECTRICAL CHARACTERISTICS

current:	2.5A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



current: - - -
 voltage: - - -
 FILE: - - -

MATERIALS

housing: PA - UL 94 V0
 screw: Galvanized steel
 clamp/spring: Nickered copper alloy
 terminal: n/a

AVAILABLE COLOURS

 (STD)
 other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
01	MPF01-10	N/A	N/A	N/A
02	MPF02-10	N/A	N/A	N/A
03	MPF03-10	N/A	N/A	N/A
04	MPF04-10	N/A	N/A	N/A
05	MPF05-10	N/A	N/A	N/A