

Type	Measurement method	Ranging Distance [m]	Accuracy (Typ)	Ranging Frequency (Typ.) [Hz]	Scan Frequency [Hz]	Field of View (Typ.) [°]	Interface	Operating Temperature [°C]	Max. External Illuminance [lux]	Supply Voltage [V]	Current Consumption [mA]	Dimensions [mm]	IP
HP60C	Depth Camera	0,2...4	±2mm at 1m (Plane accuracy)	-	-	73,8° H 58,8° V 86,4° Diagonal	USB 2.0	-10...50	-	5 (USB VBUS)	300	89 x 19 x 25	-
SDM15	ToF	0,05...15	±20mm (<1m) ±3% (1...2m) ±4% (2...15m)	10...1 800 hz	-	Single point	UART	-10...50	60 000	4,8...5,2	100	45 x 19 x 24	-
T-mini PLUS	ToF	0,05...12	±20mm (0,05...12m)	4 000	6...12	360° H	UART	-10...45	60 000	4,8...5,2	340	39 x 39 x 34	-
TEA	ToF	0,05...25	±30mm, Min.	30 000	10...30	300° H	Ethernet 10/100Mbit	0...50	80 000	9...28	167 @ 12V	53 x 53 x 82	IP65
TG15	ToF	0,05...15	±60mm (0,05...5m) ±40mm (5...15m)	20 000	5...12	360° H	UART	0...50	100 000	4,8...5,2	340	D76 x 35	IP65
TG30	ToF	0,05...30	±60mm (0,05...5m) ±40mm (5...20m) ±100mm (20...30m)	20 000	5...12	360° H	UART	0...50	100 000	4,8...5,2	340	D76 x 35	IP65
TG50	ToF	0,05...50	±60mm (0,05...5m) ±40mm (5...20m) ±100mm (20...30m) ±150mm (30...50m)	20 000	5...12	360° H	UART	0...50	100 000	4,8...5,2	340	D76 x 35	IP65
TIA-H	ToF	0,05...10	±30mm	200 000...300 000	100...150	200° H	Ethernet 10/100Mbit	-10...50	80 000	9...28	400 @ 12V	53 x 53 x 82	IP65
G2	Triangulation	0,12...16	±20mm (<1m) ±2% (1...8m)	5 000	5...12	360° H	UART	0...50	2 000	4,8...5,2	350	D74 x 43	-
G4	Triangulation	0,28...16	±20mm (<1m) ±2% (1...8m)	9 000	5...12	360° H	UART	0...50	2 000	4,8...5,2	350	D72 x 41	-
GS2-T850 (T808)	Triangulation	0,025...0,3	±3mm (<100mm) ±3% (100...200mm) ±8% (200...300mm)	10...28	-	104° H	UART	-10...40	25 000	3,2...3,4	95	26 x 24 x 11	-
X2	Triangulation	0,12...8	±20mm (<1m) ±3,5% (1...6m)	3 000	5...8	360° H	UART	0...40	2 000	4,8...5,2	300	96 x 60 x 50	-
X4	Triangulation	0,12...10	±20mm (<1m) ±3,5% (1...6m)	5 000	6...12	360° H	UART	0...40	2 000	4,8...5,2	350	102 x 66 x 58	-
X4 Pro	Triangulation	0,12...10	±20mm (<1m) ±3,5% (1...6m)	5 000	6...12	360° H	UART	0...40	40 000	4,8...5,2	330	111 x 71 x 52	-