



Product information

Weller®

WXR 3031

Code No. : **T0053502699**

Reworkstation

Rework station 3 channels, 230 V, 420 W with hot air iron WXHAP 200, 200 W, desoldering iron WXDP 120, 120 W and soldering iron WXP 120, 120 W with Power-Response Heating Technology

Technical Data



This station is ESD safe.

Dimensions L x W x H:	273 x 235 x 102 mm (10,75 x 9,25 x 4,02 inch)
Weight:	ca. 6,7 kg
Mains supply voltage:	230 V, 50 Hz / 120 V, 60 Hz / 100 V 50/60 Hz
Power consumption:	420 W (600 W)
Safety class:	I, antistatic housing III, soldering tool
Fuse:	Overcurrent release 230 V; 2,0 A 120 V; 4,0 A
Temperature accuracy:	± 9°C (± 17°F) depends on tool (WXHAP ± 30°C / ± 80°F)
Temperature stability:	± 2°C (± 4°F)
Equipotential bonding:	Via 3.5 mm pawl socket on back of unit
Display:	240 x 88 dots / Backlighting
USB-Schnittstelle:	The control unit comes with a USB port for installing firmware updates, configuration and monitoring.
Built in pump:	(Intermittent operation 30/30 s) Max. vacuum: 0,7 bar Max. flow: 18l/min Hot air max. 15 l/min

**Additional vacuum
pump:**

Max. vacuum: 0,7 bar
Max. flow: 18l/min

Weller®